



AGM
GLOBAL
VISION

ASP TM-384

THERMAL IMAGING MONOCULAR



The Asp TM-384 handheld observational thermal monocular is equipped with a 384 × 288 infrared detector and a 1024×768 OLED display. It supports functions of observation, hot spot tracking, distance measurement, Wi-Fi hotspot, and so on. The high-sensitivity built-in thermal detector provides you with clear view even in total darkness. The monocular is mainly applied to scenarios such as patrolling, law enforcement, searching and rescuing, drug enforcement, anti-smuggling, criminal seizing, hiking, travel, and hunting, etc.

- **384 × 288 resolution, high sensitivity detector**
- **Adaptive AGC, DDE, 3D DNR**
- **1024 × 768 resolution 0.39-inch OLED display**
- **Wi-Fi hotspot**
- **Built-in rechargeable Li-Ion battery**
- **Up to five hours continuous running (with Wi-Fi hotspot function off)**
- **Limited 3-year warranty**

FUNCTIONS

Distance Measurement:

The device realizes distance measurement function after marking the top and bottom of target, and input the target height.

Hot Spot Mark:

The device detects and marks the hot spot of highest temperature.

Mode Switch:

Device supports pallet switch and distance measurement.

Storage:

Built-in memory module supports video recording/snapshot capturing.

Digital Zoom:

Device supports 1× and 2× digital zoom.

Wi-Fi Hotspot:

Device can capture snapshots, record videos, and set parameters via APP after being connected to your phone.



Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.

SPECIFICATIONS

| | Asp TM25-384 | Asp TM35-384 |
|--------------------------|--|--|
| Image Sensor | Vanadium Oxide Uncooled Focal Plane Arrays | Vanadium Oxide Uncooled Focal Plane Arrays |
| Resolution | 384 x 288 | 384 x 288 |
| Detector Pitch | 17um | 17um |
| Response Wavebond | 8um to 14um | 8um to 14um |
| NETD | < 35mk (@25°C, F#=1.0) | < 35mk (@25°C, F#=1.0) |
| Lens Focal Length | 25mm | 35mm |
| Field of View | 14.9° x 11.2° | 10.7° x 8° |
| F-number | 1.0 | 1.0 |
| Optical Magnification | 1.7x | 2.4x |
| Digital Zoom | 2x | 2x |
| Palettes | Black hot, White hot, Red hot, Fusion | Black hot, White hot, Red hot, Fusion |
| Monitor | 0.39-inch, OLED, 1024 x 768 | 0.39-inch, OLED, 1024 x 768 |
| Hot Track | Yes | Yes |
| Storage | Built-in memory module (16GB) | Built-in memory module (16GB) |
| Record Video | Support on-board video recording | Support on-board video recording |
| Capture Snapshot | Yes | Yes |
| Wi-Fi | Yes | Yes |
| Battery | Buit-in rechargeable Lithium battery | Buit-in rechargeable Lithium battery |
| Battery Operating Time | Up to 5 hours continuous running | Up to 5 hours continuous running |
| Battery Capacity Display | Yes | Yes |
| Power | 5V DC/2A, 2W | 5V DC/2A, 2W |
| Working Temperature | -30°C to 55°C (-22°F to 131°F) | -30°C to 55°C (-22°F to 131°F) |
| Protection Level | IP67 | IP67 |
| Dimensions | 189 x 74 x 66 mm (7.4 x 2.9 x 2.6 in) | 202 x 74 x 66 mm (7.9 x 2.9 x 2.6 in) |
| Weight | 460 g (16.2 oz) | 480 g (16.9 oz) |

Specifications are subject to change without notice.



MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA
Tel. +1.928.333.4300 | Fax +1.480.393.4882 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | Andrey Lyapchev #7 | Sofia, P.C. 1756 | Bulgaria
Tel. +44.292.255.0509 | info@agmglobalvision.eu | www.agmglobalvision.eu

www.agmglobalvision.com